

TPE-500 PROPANE Heater Package

Treats up to 1500 sq. ft.



(1) TPE-500

500,000 BTU Direct Fired Propane or Natural Gas heater with Rego temperature adjusting valve or thermostatically controlled configuration.



(1) Rego Valve

Adjustable brass valve attached to pipe train of TPE-500 heater for precise temperature control.



(1) Gas Hose

20' x 3/8" flexible gas hose with 10 psi (red) regulator that attaches with quick connects to the heater.



(1) Duct Adapter

18" adapter with 3 clasps that attached to the front of the TPE-500 heater.



(1) Mylar Duct

18" x 25' duct that attaches to the end of the duct adapter.



(1) Pigtail

Allows multiple propane tanks to be linked together.



(1) T-Block

Attaches to propane cylinder which allows multiple propane tanks to be linked together.



(1) Tegam Thermometer

Used to monitor temperature to target pests throughout the structure.




(1) Tegam 6 Way Switch Box

Attached to the top of the thermometer and accepts 6 thermocouple probes.



(6) Thermocouple Probes

50' probes that attach to switch box for interior temperature monitoring (also available in 100')



(4) High Temperature Fan

20" fan used to circulate the heat evenly throughout the structure.

Pest-Heat equipment and training programs are available nationwide!

PEST-HEAT

A Safe & Chemical Free Heat Alternative™

CALL TODAY AT 877-234-5630 OR VISIT WWW.PESTHEAT.COM